

Properly dried channels reduce the risk of infection.

Studies indicate there is a strong correlation between moisture and microbe colonization within flexible endoscopes.

The Airtime™ Flexible Scope Dryer uses filtered air to dry the air/water and suction channels after automated reprocessing. It ensures scopes are not stored or put into immediate use with wet channels. Properly drying channels reduces the risk of infection.

- **Airtime uses HEPA filtered air to dry the air/water, suction and auxiliary water channels after automated reprocessing. Also available with a medical grade air option.**
- **Uses two independent pumps and timers that will dry two scopes simultaneously. Air pressure will not drop when you begin drying a second scope.**
- **Airtime's dual screen allows for two scopes to be dried with independent start and stop times.**
- **Restricted channel sensors will immediately shutoff the Airtime pump and alert the user of a potentially clogged channel.**
- **Available options: IV pole mounted, wall mounted or on a table stand (shown in the photo on the left).**



ATSD01
Airtime™ Flexible Scope Dryer
Two pump system



Daily Universal Tubing Sets
Easily and quickly changed out.

VT100

Daily tubing set for flexible endoscopes. Tubing sets are universal and can be used with Olympus, Pentax and Fuji scopes by selecting the appropriate adapters.



Port Adapters

Available for suction port, air/water port, biopsy port, and auxiliary water jet.

ASO1 – Olympus Adapter Set 1

2 Suction/Air Water Adapters
1 Biopsy Adapter

ASO2 – Olympus Adapter Set 2

2 Suction/Air Water Adapters
1 Biopsy Adapter
1 Auxiliary Water Adapter



Disposable Adapters

Prevents potential cross-contamination of ports.

See page 2 for IV pole mounting options.

IV Pole Mount | Components



IV100 – Scope Cradle Bar

Will hold two flexible endoscopes. The Scope Cradle Bar and bracket assembly attaches to the 3/4" upper section of most standard IV poles. Smooth powder-coated finish.



IV200 – Height Reduction Bars

Allows the height of the Scope Cradle Bar to be lowered to a more comfortable height while keeping the scope distal tip at a safe height. A lower height makes the replacement of daily tubing and adapter sets easier. Attaches to the 1" lower section of most standard IV poles.



IV300 – IV Pole Mounting Bracket

Attach the Airtime Control Unit to any standard IV pole.

IV Pole with Height Reduction Bars (6' working height)



IV Pole without Height Reduction Bars (7.5' full height)

SPECIFICATIONS

COMPATIBLE ENDOSCOPES

Olympus and Pentax Flexible Endoscopes

CONTROL UNIT DIMENSIONS

10" H x 6" W x 4" D

CONTROL UNIT WEIGHT

4.4 lbs

ELECTRICAL CHARACTERISTICS

- 100 – 240 VAC, 50 – 60 Hz
- UL, CE
- DoE Energy Efficiency Level VI
- CE Marked
- IEC 60601-1 Medical Grade

FEATURES

- Dual Timer Screens
- Dual Independent Operating Pumps
- Adjustable Timer Settings
- Dual Over Pressure Channel Sensors
- .1µ HEPA Filtration
- Universal Mounting Bracket
- Filter Replacement Alert